

**Vehicle and Equipment Intergration Solutions** 





### **Basic Kit Configuration**

Strike-Kit component package varies by model. See vehicle model page for component configuration.

#### RP STRIKE-KIT COMPONENTS

- RP Super Grit texture coating, tan, black, camo, custom colors available
- RP high-capacity, multi-modal tactical payload flatbed with lower storage
- RP multi-modal tailgate system for multiple tactical payload track configurations with optional MEDEVAC integration\* on 4-seat models
- RP tactical assault front pusher bumper with strut integrated payload track system and aerial transport tie-downs
- RP rear push bumper assembly with aerial transport tie-downs
- Upgraded suspension for high payload operations
- RP SOF Series II, IV, IV Magnum and SOF Spartan run-flat and performance tires
- ITP Delta 12 or 14" steel wheels
- Raceline beadlock wheels
- RP Fatigue Mitigation Tactical Seat System (MOLLE, 1000D Cordura®)
- RP Fatigue Mitigation Tactical Rear Folding Seat System with best-in-class leg room for Stokes/NATO litter carriage in bed (1000D Cordura®)
- RP Soft Top (MOLLE, 1000D Cordura®)
- RP Soft Door Panels (MOLLE, 1000D Cordura®)
- Lithium Iron Phosphate battery for extended 12VDC capacity
- Emergency Lithium power pack for vehicle recovery
- Forward/rear 2-inch receivers



### **RP STRIKE-KIT RECOMMENDED OPTIONS**

- RP high-load tactical team standoff nerf bar assembly/ rock slider with stow mode for aerial transport
- RP modular ammo/fuel can/payload assembly
- Beadlock wheels
- Elka high-performance shock absorbers
- Baja Designs driving/blackout/IR lights & light bars
- Additional 12VDC and 24VDC outlets

### **RP STRIKE-KIT OPTIONS**

- RP Powdercoating, custom colors available
- HydroGraphic finishes, custom colors and patterns available
- Narrowing kit: A-arms and trailing arms
- RP modular front cargo rack
- RP quick release articulating roll cage assembly for internal aerial transport
- RP SOF Series II, IV, IV Magnum, SOF Spartan run-flat and performance tires
- Apache 360 LT track and mounting kit
- Selectable RODS (Rear Open Differential)
- RP keyless ignition system
- HID/LED light illumination
- Integrated seat hydration packs
- RP 4-point static harness with quick release
- SatFi communication system/bundle
- Antenna mount
- Half and Full windshields
- RP MEDEVAC integration\*
- RP litter restraint, multi-modal and configurable rail system\*
- PowerAll<sup>®</sup> jump start system
- RP initial spare parts kit
- RP 4X4 to 4X6 TAG axle extension
- Self-extracting 4500 lb winch

<sup>\*</sup>NOTE: Does not include litter/stretcher device. Must be purchased separately.

## RP Strike-G<sub>th</sub> RP Strike-G4<sub>th</sub> RP G2<sub>th</sub>

variant Can-Am Commander



	RPAMS STRIKE-C/C2/C4 STANDARD 2019 SPECIFICATIONS			
	CAN-AM 1000R DPS ENGINE   92 HP			
Туре		92 Hp, Rotax® 976 cc, v-twin, liquid-cooled		
Fuel Deliver System	У	Intellegent Throttle Control (iTC) with Electronic Fuel Injection (EFI)		
Transmissio	on	CVT, L / H / N / R / P, standard engine braking		
Drive Train Selectable 2WD / 4WD with Visco-Lok <sup>†</sup> QE auto-locking front diffe				
Power Stee	ring	Tri-Mode Dynamic Power Steering (DPS™)		
		CHASSIS		
Frame		Steel		
Cage Type		2-in / 5.1 cm diameter, high-strength steel, ROPS-approved		
Steering Wh Adjustment		Strike-C: Adjustable tilt steering Strike-C4: N/A		
Front Suspe Type/Travel		Double A-arm with sway bar / 10 in (25.4 cm)		
Rear Susper Type/Travel	nsion I	Torsional Trailing arm Independent (TTI) with external sway bar / 10 in (25.4 cm)		
Shocks		Upgraded shocks for high payload operations		
Front Brake	;	Dual 214 mm (C4/220 mm) ventilated disc brakes with hydraulic twin-piston calipers		
Rear Brake		Strike-C: Single 214 mm ventilated disc brake with hydraulic twin-piston calipe Strike-C4: Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers		
Tires Front/	'Rear	RP SOF Series II, 12-PLY, Run-Flat, 26x9x12 in / 66x22.9x30.5 cm		
Wheels		ITP Delta 12" steel wheels, black		
		WEIGHT/DIMENSIONS		
Dry Weight		1,700 lb to 1,950 lb / 771.1 kg to 884.5 kg		
L x W x H (in)  Strike-C: 123 x 60 x 72 in 123 x 60 x 60 in with retracted roll cag 152 x 60 x 60 in with retracted roll cag 152 x 60 x 60 in with retracted roll cag				
L x W x H (cm) 312.42 x 152. Strike-C4: 386.08 x 152		Strike-C: 312.42 x 152.4 x 182.9 cm 312.42 x 152.4 x 152.4 cm with retracted roll cage Strike-C4:386.08 x 152.4 x 193 cm 386.08 x 152.4 x 152.4 cm with retracted roll cage		
Wheelbase		Strike-C: 75.8 in / 192.4 cm Strike-C4: 106.1 in / 269.4 cm		
Ground Clearance	ound 11 in / 27.9 cm			
		Total: 8.3 gal (31.6 L) Glove box: 4.5 gal / 17.2 L Center console: 0.3 gal / 1.3 L		
Fuel Capaci	ty	10 gal / 37.8 L		
Payload Cap	pacity	Strike-C/C2: 1,500 lb / 680 kg Strike-C4: 2,000 lb / 907.2 kg		
Rear Cargo	L	Strike-C/C4 Dual-Level Cargo Box: 1,000 lb / 453.6 kg Upper Level: 800 lb / 362.9 kg, Lower Level: 200 lb / 91 kg		
Bed Capaci		RP C2 w/BRP Dual-Level Cargo Box: 600 lb / 272 kg Upper Level: 400 lb / 181 kg, Lower Level: 200 lb / 91 kg		
Optional Fro Rack Capac	ity	250 lb / 113.4 kg		
Towing Capa	acity	1,500 lb / 680 kg		
	BASIC	RP Strike-C & RP Strike-C4 ADDITIONAL FEATURES/UPFITS		
Exterior Pai	int	RP Super Grit Coating, Tan, Black, Camo		
Multifunction Digital: Speedometer, tachometer, odometer, tri		Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECOTM mode, seat belt and $4\times4$ indicator, diagnostics, clock, auto shut off		
Anti-Theft System		Digitally Encoded Security System (D.E.S.S.TM)		
Electrical Prewired for winch		Prewired for winch		
Lighting		240-W from four 60-W projectors with tail lights/brake lights		
5 - 5				

RPA	RPAMS STRIKE-C/C2/C4 STANDARD 2019 SPECIFICATIONS		
BASIC RP C2 (Command & Control) ADDITIONAL FEATURES/UPFITS continued			
Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)		
Exterior Accessories	High-Capacity, multi-modal tactical payload flatbed with lower storage, multi-modal tailgate system for multiple tactical payload track configurations, tactical assault front push bumper with strut integrated payload track system and aerial transport tie-downs, rear push bumper with aerial transport tie-downs *MEDEVAC integration system - C4 ONLY		
Interior	RP Fatigue Mitigation Tactical Seat System, MOLLE, 1000D Cordura®		
Roof	RP Soft Roof, MOLLE, 1000D Cordura®		
C4 Rear Seating	Rear seating with Best-In-Class leg room for rapid egress/ingress, fold forward for Stokes/NATO litter carriage in bed		
Protection	Strike-C: N/A Strike-C4: Mudguards, w/BRP bed includes rails		
Exterior Paint	RP Powdercoat, Matte Black		
Guage	Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECOTM mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off		
Anti-Theft System	Digitally Encoded Security System (D.E.S.S.TM)		
Electrical	Prewired for winch		
Lighting	240-W from four 60-W projectors with tail lights/brake lights		
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)		
Exterior Accessories	Tactical assault push bumper with strut integrated payload track system and aerial transport tie-downs		
Interior	RP Fatigue Mitigation Tactical Seat System, MOLLE, 1000D Cordura®		
Roof	RP Soft Roof, MOLLE, 1000D Cordura®		
Battery	Lithium Iron Phosphate, extended 12VDC capacity		
Emergency Power	Lithium power pack for vehicle recovery		
	WARRANTY		
Factory 6 months limited warranty			

RPAMS STRIKE-C/C2/C4 OPTIONAL EQUIPMENT	
RECOMMENDED OPTIONS	
High-Load tactical team standoff nerf bar/rock slider with stow and lock mode for air transport	

RPAMS STRIKE-C/C2/C4 OPTIONAL EQUIPMENT		
ADDITIONAL FEATURE OPTIONS		
Modular Storage   RP modular ammo/fuel can/payload assembly		
Wheels	Beadlock wheels	
Shocks/ Suspension	Elka high-performance shocks	
Lighting	Baja Designs blackout/IR lights & light bars	
Power	Additional 12VDC & 24VDC outlets	
Coating	RP Powdercoat, HydroGraphic Finishes, custom colors and patterns available	
Narrowing Kit	A-arms and trailing arms	
Cargo Rack	RP modular front cargo rack assembly	
Roll Cage	Quick release articulating roll cage with internal aerial transport	
Tires	RP SOF Series II, 12-PLY, Run-Flat, 26x9x14 in / 66x22.9x35.6 cm	
Tracks	Tracks Apache 360 LT Track System and mounting kit	
Drive Train Selectable RODS (Rear Open Differential System)		
Ignition	RP keyless ignition	
Lighting	HID/LED light illumination	
Hydration Seat	Integrated seat hydration packs	
Harness	RP 4-point static harness with quick release	
Communication	SatFi communication system/bundle	
Accessories	Antenna mount	
Windshield	Half windshield	
MEDEVAC*	MEDEVAC Integration	
RP Litter System*	RP litter restraint, multi-modal and configurable rail system	
Jumper	PowerAll® Jump Start System	
TAG Axle Extension	4X4 to 4X6 conversion, removable TAG extension Payload Capacity: 1,500 lb / 680 kg	
Spare Parts Kit	Initial spare parts kit	
Winch	Self-extracting 4500 lb winch	





RPAMS STRIKE-M/M4 STANDARD 2018 SPECIFICATIONS			
Can-Am 1000R ENGINE   101 HP	Can-Am 1000R ENGINE   101 HP		
Type 101 hp, 1000R Rotax® 976 cc, V-twin with high-flow dynamics, li Mid-engine layout for mass centralization	quid-cooled.		
Fuel Delivery System Intelligent Throttle Control (iTC) with Electronic Fuel Ignition (E	FI)		
<b>Transmission</b> CVT with Zylon-reinforced belt, L/H/N/R/P, standard engine	CVT with Zylon-reinforced belt, L / H / N / R / P, standard engine braking		
<b>Drive Train</b> Selectable 2WD / 4WD with Visco-Lok <sup>†</sup> QE auto-locking front di	fferential		
Power Steering Tri-Mode Dynamic Power Steering (DPS™)  CHASSIS	-		
Frame Steel			
Cage Type 2-in / 5.1 cm diameter, high-strength steel, ROPS-approved			
Steering Wheel Adjustable tilt steering Adjustment			
Front Suspension Type/Travel  Double A-arm with sway bar / 14 in (35.6 cm)	Double A-arm with sway bar / 14 in (35.6 cm)		
Rear Suspension Type/Travel  Torsional Trailing A-arms (TTA) independent with sway bar / 14 in	n (35.6 cm)		
Shocks Upgraded shocks for high payload operations			
Front Brake Dual 220 mm ventilated disc brakes with hydraulic twin-piston	•		
Rear Brake Dual 214 mm ventilated disc brakes with hydraulic single-piston	· · · · · · · · · · · · · · · · · · ·		
Tires Front/Rear RP SOF Series II, 12-PLY, Run-Flat, 26x9x12 in / 66x22.9x30.5 c	em		
Wheels ITP Delta 12" steel wheels, black			
WEIGHT/DIMENSIONS			
Strike-M: 129 x 64 x 74.2 in 129 x 60 x 60 in with narrowing kit & retracted roll ca Strike-M4: 159 x 64 x 78 in	129 x 60 x 60 in with narrowing kit & retracted roll cage		
Strike-M: 327.66 x 162.5 x 188.54 cm 327.66 x 152.4 x 152.4 cm with narrowing kit & retrac Strike-M4: 403.86 x 162.5 x 198 cm 403.86 x 152.4 x 152.4 cm with narrowing kit & retrac	_		
Wheelbase         Strike-M: 84.3 in / 214.1 cm         Strike-M4: 113.8 in / 285	9.1 cm		
Ground Clearance Strike-M: 13 in / 33 cm Strike-M4: 12.5 in / 31.8	5 cm		
Cockpit Storage Glove box: 4.5 gal / 17.2 L Under driver seat: 3.5 gal / 13.1 L (M Center console: 0.3 gal / 1.3 L	only)		
Fuel Capacity 10 gal / 37.8 L			
Payload CapacityStrike-M: 1,500 lb / 680 kgStrike-M4: 2,000 lb / 90	07.1 kg		
Rear Cargo Bed Capacity  RPAMS Rear Bed: 1,000 lb / 453.6 kg BRP Standard Bed: 200 lb / 91 kg (Strike-M4 150 lb / 68 kg) with LinQ quick-attach			
Optional Front Rack Capacity 250 lb / 113.4 kg			
Towing Capacity RPAMS Rear Bed: 1,500 lb / 680 kg BRP Standard Bed: N/A			
ADDITIONAL FEATURES			
Exterior Paint RP Super Grit Texture Coating, Tan, Black, Camo			
Guage  Multifunction Digital: Speedometer, tachometer, odometer, trip ters, fuel, gear position, sport mode, ECO™ mode, seat belt and diagnostics, clock, auto shut off	and hour me-		
	TX Tillulcator,		
Anti-Theft System Digitally Encoded Security System (D.E.S.S.™)	TATIIIIIIGALUI,		
Anti-Theft System     Digitally Encoded Security System (D.E.S.S.™)       Electrical     Prewired for Winch	TXTIIIIIGALOI,		
	TATIIIIIGALUI,		

RPAMS STRIKE-M/M4 STANDARD 2018 SPECIFICATIONS		
ADDITIONAL FEATURES continued		
Exterior Accessories  High-capacity, multi-modal tactical payload flatbed, multi-modal tailgate system for multiple tactical payload track configurations, tactical assault from push bumper with strut integrated payload track system and aerial transportie-downs, forward/rear 2" receiver, Passenger handhold and grab bar  *MEDEVAC integration system - M4 ON		
Interior	RP Fatigue Mitigation Tactical Seat System, MOLLE, 1000D Cordura®	
Roof	f RP Soft Roof, MOLLE, 1000D Cordura®	
M4 Rear Seating  Rear seating with Best-In-Class leg room for rapid egress/ingress, fold forward for Stokes/NATO litter carriage in bed		
Protection N/A		
WARRANTY		
Factory	6 months limited warranty	

RPAMS STRIKE-M/M4 OPTIONAL EQUIPMENT		
RECOMMENDED OPTIONS		
Exterior Accessories	High-Load tactical team standoff nerf bar/rock slider with stow and lock mode for air transport	
Modular Storage RP modular ammo/fuel can/payload assembly		
Wheels Beadlock wheels		
Shocks Elka high-performance shocks		
Lighting	Lighting Baja Designs driving/blackout/IR lights & light bars	
Power	Additional 12VDC & 24VDC outlets	

RPAMS STRIKE-M/M4 OPTIONAL EQUIPMENT		
ADDITIONAL FEATURE OPTIONS		
Coating	RP Powdercoat, HydroGraphic Finishes, custom colors and patterns available	
Narrowing Kit	A-arms and trailing arms	
Cargo Rack	RP modular front cargo rack assembly	
Cage	Quick release articulating roll cage assembly for internal aerial transport	
Tires	RP SOF Series II, 12-PLY, run-flat, 26x9x14 in / 66x22.9x35.6 cm	
Tracks	Apache 360 LT Track System and mounting kit	
Drive Train	Selectable RODS (Rear Open Differential System)	
Ignition	RP keyless ignition	
Lighting	HID/LED light illumination	
Hydration Seat	Integrated seat hydration packs	
Harness	RP 4-point static harness with quick release	
Communication	SatFi communication system/bundle	
Accessories	Antenna mount	
Windshield	Half windshield	
MEDEVAC*	MEDEVAC Integration	
RP Litter System*	RP litter restraint, multi-modal and configurable rail system	
Jumper	PowerAll® Jump Start System	
Spare Parts Kit	Initial spare parts kit	
Winch	Self-extracting 4500 lb winch	

 $<sup>\</sup>verb§^*NOTE: MEDEVAC Integration \& RP Litter System does not include litter/stretcher device. Must be purchased separately.$ 





RPAMS STRIKE-X/X4 STANDARD 2019 SPECIFICATIONS		
Can-A	Am TURBOCHARGED TRIPLE-CYLINDER ENGINE   120/172 HP	
Туре	120/172 Hp, Rotax® 900 cc, ACE (Advanced Combustion Efficiency) turbocharged triple-cylinder engine, liquid cooled with Donaldson high performance air filter / 172 Hp engine includes integrated intercooler	
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Ignition (EFI)	
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P	
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>+</sup> X auto-locking front differential	
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)	
CHASSIS		
Cage/Chassis	Dual-phase 980 steel, fully welded	
Front Suspension Type/Travel	Double A-arm with sway bar / 20 in (50.8 cm)	
Rear Suspension Type	4-Link Torsional Trailing-arm X (TTX) with sway bar / 20 in (50.8 cm)	
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment	
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and bottom-out control	
Front Brake	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear Brake	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers	
Tires Front/Rear	RP SOF Series IV Magnum, 8-PLY, 30x10x14 in / 76.2x25.4x35.56 cm	
Wheels	Raceline 14" Black Mambo Beadlock Wheels with extended lug nuts	
	WEIGHT/DIMENSIONS	
Dry Weight	1,790 lb to 1,990 lb / 811.93 kg to 902.65 kg	
LxWxH(in.)	Strike-X: 146 x 67 x 66 in Strike-X4: 179 x 67 x 66 in :	
LxWxH(cm)	Strike-X: 370.8 x 170.2 x 167.6 cm Strike-X4: 454.7 x 170.2 x 167.6 cm	
Wheelbase	Strike-X: 102 in / 259.1 cm Strike-X4: 135 in / 342.9 cm	
Ground Clearance	Strike-X: 14 in / 35.6 cm Strike-X4: 13 in / 33 cm	
Cockpit Storage	Strike-X: Total - 2.5 gal / 9.4 L Glove box: 1.6 gal / 6.2 L Center console: 0.8 gal / 2.8 L Cup holders: 0.1 gal / 0.4 L Strike-X4: Total - 3 gal / 11.4 L Glove box: 1.6 gal / 6.2 L Center console: 1.1 gal / 4.1 L Cup holders: 0.3 gal / 1.1 L	
Fuel Capacity	10.5 gal / 37.8 L	
Payload Capacity	1,000 lb / 453.6 kg	
Rear Bed Dimen- sions/ Capacity	48.5 (W) x 38 (L) x 66 in (H) 1,000 lb / 453.6 kg with Elka Suspension and RP SOF Series Tires	
Optional Front Rack Capacity	250 lb / 113.4 kg	
Towing Capacity	RPAMS Rear Bed: 1,500 lb / 680 kg BRP Standard Bed: N/A	
	ADDITIONAL FEATURES	
Exterior Paint	RP Super Grit Coating, tan, black, camo	
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button	
Guage	Multifunction Analog/Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode/ECO mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	
Electrical	Prewired for winch	
	indicator, diagnostics, clock, auto shut off	

RPAMS STRIKE-X/X4 STANDARD 2019 SPECIFICATIONS			
	ADDITIONAL FEATURES continued		
Lighting	LED headlignts and tail lights with unique Can-Am LED signature		
Instrumentation	Lighter type DC outlet in central console		
Exterior Accessories	High-capacity multi-modal tactical payload flatbed, multi-modal tailgate system for multiple tactical payload track configurations, tactical assault front push bumper with strut integrated payload track system and aerial transport tie-downs, forward/rear 2" receiver, Passenger handhold and grab bar *MEDEVAC integration system - X4 ONLY		
Roof	RP Soft Roof, MOLLE, 1000D Cordura®		
Door Panels	RP Soft Quarter Door Panels, MOLLE, 1000D Cordura®		
Protection	Integrated front bumper, full High Molecular Weight (HMW) skid plate		
WARRANTY			
Factory	Factory 6 months limited warranty		
RPAMS STRIKE-X/X4 OPTIONAL EQUIPMENT			
RECOMMENDED OPTIONS			
Modular Storage	RP modular ammo/fuel can/payload assembly		
Shocks	Elka Suspension model specific Stage 5 race-level high-performance shocks		
Lighting	Baja Designs driving/blackout/IR lights & light bars		

RPAMS STRIKE-X/X4 OPTIONAL EQUIPMENT		
ADDITIONAL FEATURE OPTIONS		
Power	Additional 12VDC & 24VDC outlets	
Coating	RP Powdercoat, HydroGraphic Finishes, custom colors and patterns available	
Cargo Rack	RP modular front cargo rack assembly	
Tires	RP SOF Spartan Series, 12-PLY, Front: 29x9x14/73.7x22.7x35.6 cm & Rear: 29x11x14/73.7x28x35.6 cm	
Wheels	Beadlock wheels	
Lighting	HID/LED light illumination	
Communication SatFi communications system/bundle		
Accessories	Antenna mount	
Windshield	Half & Full windshields	
MEDEVAC*	Integration	
RP Litter System*	RP litter restraint, multi-modal and configurable rail system	
Jumper	PowerAll® Jump Start System	
Spare Parts Kit	Initial spare parts kit	
Winch	Self-extracting 4500 lb winch	

<sup>\*</sup>NOTE: MEDEVAC Integration & RP Litter System does not include litter/stretcher device. Must be purchased separately.





	Ri	PAMS STRIKE-D3/D6 STANDARD 20	19 SPECIFICATIONS	
	Can-Am HD10 ENGINE   72 HP			
	Туре	72 Hp, Rotax® 976 cc, v-twin, liquid-co	oled	
	Fuel Delivery System	Intelligent Throttle Control (iTC) with I	Electronic Fuel Ignition (EFI)	
	Transmission	PRO-TORQ transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection, Extra-L/H/N/R/P		
	Drive Train	Lockable rear differential and Visco-Lok <sup>†</sup> QE auto-locking front differential		
THE PERSON NAMED IN	Driving Assistance	Strike-D3: Electronic Hill Descent Control with ECO / Work / Normal modes Strike-D6: Electronic Hill Descent Control		
	Power Steering	Dynamic Power Steering (DPS™)		
		CHASSIS		
	Frame	Steel		
	Cage Type	ROPS-approved profiled cage. Certifie	d ISO 3471 and OSHA	
	Steering Wheel Adjustment	Adjustable tilt steering		
	Front Suspension Type/Travel	Double A-arm / 10 in (25.4 cm)		
1	Rear Suspension Type	Torsional Trailing A-arms (TTA) with ex	ternal sway bar / 10 in (25.4 cm)	
	Shocks	Upgraded shocks for high payload ope	rations	
	Front Brake	Dual 220 mm ventilated disc brakes w	ith hydraulic twin-piston calipers	
	Rear Brake	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers (Strike-D6: twin-piston calipers)		
	Tires Front/Rear	RP SOF Series II, 12-PLY, Run-Flat, 26x9x14 in / 66x22.9x35.6 cm		
	Wheels	14" Wheels, black		
		WEIGHT/DIMENSION	NS .	
	Dry Weight	Strike-D3: 1,614-1,950 lb / 732-885 kg Strike-D6: 1,857-1,950 lb / 842-885 kg		
	Person Capacity	Strike-D3: 3	Strike-D6: 6	
	L x W x H (in)	Strike-D3: 124.2 x 62 x 78 in	Strike-D6: 154.5 x 63.5 x 76 in	
	L x W x H (cm)	Strike-D3: 315.5 x 157.5 x 198.1 cm	Strike-D6: 392.4 x 161.2 x 193 cm	
	Wheelbase	Strike-D3: 83 in / 210.82 cm	Strike-D6: 115.5 in / 293.37 cm	
	Ground Clearance	11 in / 28 cm		
THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.	Cockpit Storage	Strike-D3Total: 16.2 gal / 61.3 L Under Dash: 6 gal / 22.8 L Dash: 2 gal / 7.7 L Armrests & cup holders: 0.9 gal / 3.5 L Water-resistant/removable toolbox: 1.7 gal / 6.3 L Waterproof/removable box (under passenger seat): 5.6 gal / 21 L	Strike-D6 Total: 11.1 gal / 42.1 L Under Dash: 6 gal / 22.8 L Dash: 1.8 gal / 6.98 L Armrests & cup holders: 1.6 gal / 6.1 L Water-resistant/removable toolbox: 1.7 gal / 6.3 L	
The state of the s	Fuel Capacity	10.6 gal / 40 L		
	Payload Capacity	Strike-D3: 1,750 lb / 794 kg	Strike-D6: 2,000 lb / 907 kg	
	Rear Cargo Bed Capacity	RPAMS Rear Bed: 1,150 lb / 522 kg	BRP Standard Bed: 1,000 lb / 454 kg / California Only: 600 lb / 272.2 kg	
	Optional Front Rack Capacity	250 lb / 113 kg		
1				

RPAMS STRIKE-D3/D6 STANDARD 2019 SPECIFICATIONS		
ADDITIONAL FEATURES		
Exterior Paint	RP Super Grit Coating, tan, black, camo	
Guage	Strike-D3: Multifunction Analog/Digital – Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO / Work / Normal modes, seat belt, 4x4 indicator, diagnostics, clock, auto shut off Strike-D6: Multifunction Digital – Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, seat belt, diagnostics, clock, auto shut off	
Electrical	Strike-D3: 4500 lb. (2041 kg) winch with roller fairlead Strike-D6: N/A	
Lighting	Strike-D3: 140-W output from four 35-W reflectors ensuring a wide visibility, plus LED tail lights with halo glow effect Strike-D6: 140-W output from four 35-W reflectors ensuring a wide visibility plus LED tail lights	
Instrumentation	Strike-D3: Two lighter type DC outlets, one in the console (20-A) and one in the under dash storage (20-A) Strike-D6: Lighter type DC outlet in the console (20-A)	
Magneto	650 W	
Battery	Strike-D3: 12 V (30 amp/h) Strike-D6: 12 V (18 amp/h)	
Exterior Accessories	Tactical front bumper, modular front cargo rack, dual rear NATO litter restraint system*, 2-inch hitch receiver	
Roof	RP Soft Roof, MOLLE, 1000D Cordura®	
Seating	Strike-D3: VERSA-PRO bench seat with reinforced XT seat skin and adjustable driver seat Strike-D6: Dual VERSA-PRO bench seats for 6 adults	
Protection	Strike-D3: XT front bumper, full HMW skid plate, full hard roof Strike-D6: Integrated front steel bumper, central HMW skid plate	
	WARRANTY	
Factory	6 months limited warranty	

RPAMS STRIKE-D3/D6 OPTIONAL EQUIPMENT	
	RECOMMENDED OPTIONS
Exterior Accessories	High-Load tactical team standoff nerf bar/rock slider with stow and lock mode for air transport
Modular Storage	RP modular ammo/fuel can/payload assembly
Shocks	Elka high-performance shocks
Lighting	Baja Designs driving/blackout/IR lights & light bars
Power	Additional 12VDC & 24VDC outlets
	ADDITIONAL FEATURE OPTIONS
Coating	RP Powdercoat, HydroGraphic Finishes, custom colors and patterns available
Cargo Rack	RP modular front cargo rack assembly
Tires	RP SOF Spartan Series, 12-PLY Front: 27x9x14 / 68.6x22.7x35.6 cm & Rear: 27x11x14 / 68.6x28x35.6 cm
Wheels	Beadlock wheels
Lighting	HID/LED light illumination
Hydration Seat	Integrated seat hydration packs
Communication	SatFi communication system/bundle
Accessories	Antenna mount
Windshield	Half & full windshields
MEDEVAC*	MEDEVAC Integration
RP Litter System*	RP litter restraint, multi-modal and configurable rail system
Jumper	PowerAll® Jump Start System
Spare Parts Kit	Initial spare parts kit
Winch	Self-extracting 4500 lb. winch

\*NOTE: MEDEVAC Integration & RP Litter System does not include litter/stretcher device. Must be purchased separately.





















### **RP Advanced Mobile Systems**

**Veteran and Minority Owned Business** 

11160 SW Durham Lane, Suite 3 | McMinnville, Oregon 97128 | phone: 503-434-9446 | fax: 503-217-6080

DUNS: 829928139 | TIN: 26-4447775 | CAGE code: 5D2V2

### www.RPAM5.com





# FOR MORE INFORMATION & DEALER INQUIRIES: Terry Wilmeth 971-237-3217 | Jim Baynes 503-348-7950 CustomerService@RPAMS.com